



Accesorii pentru Hyperion 1300g

Power

46-00525 STD Power Supply: NA plug, 1.0A @ 5.2VDC, 90-255VAC @ 50-60Hz

Cables

CBL-500-300-C00 STK Cable: USB, black, Type A, 3m (9.8'), coiled, 5V host power

CBL-500-300-S00 STK Cable: USB, black, Type A, 3m (9.8'), straight, 5V host power

CBL-020-300-C00 Cable: RS232 (5V signals), black, DB9 Female, 3m (9.8'), coiled, 5V external power with option for host power on pin 9 STD

CBL-120-300-C00 Cable: RS232C (+/-12V signals), black, DB9 Female, 3m (9.8'), coiled, 5V external power with option for host power on pin 9 STD

CBL-220-300-C00 Cable: RS232 (+5V signals); black, DB9 Male; 3m (9.8'), coiled, external power with option for host power on pin 9 STD

CBL-420-300-C00 Cable: RS232 Aux, black, 3m (9.8'), coiled, for connection to Honeywell Stratos scanners STD

CBL-500-500-C00 STD Cable: USB, black, Type A, 5m (16.4'), coiled, 5V host power

CBL-503-300-C00 STD Cable: USB, black, 12V locking, 3m (9.8'), coiled, 5V host power

CBL-600-400-C00 STD Cable: IBM 46xx Port 9b, 12V Power, coiled, 4m (13.1')

CBL-720-300-C00 Cable: Keyboard Wedge (KBW), black, PS2, 3m (9.8'), coiled, 5 V external power with option for host power STD

Stands/holders

STND-25F03-007-4 STK Stand: gray, 25cm (10") stand height, flexible rod, weighted mid-sized universal base, Hyperion 1300 cup

STND-23R03-006-4 STD Stand: gray, 23cm (9") stand height, rigid rod, weighted mid-sized universal base, Hyperion 1300 sliding cradle

STND-30R03-006-4 STD Stand: gray, 30cm (12") stand height, rigid rod, weighted mid-sized universal base, Hyperion 1300 sliding cradle

HOLDER-008-U STD Holder: desktop/wall mount (includes holder, screws)

Va invitam sa ne contactati pentru detalii despre toate modelele si accesoriile: office@ds-solution.ro