

# Xenon 1900h

### **Area-Imaging Scanner**

Xenon 1900h, designed specifically for healthcare, is redefining the standard for hand-held scanners. Honeywell's sixth-generation of areaimaging technology features a custom sensor that is optimized for bar code scanning. With industry-leading performance and reliability, the Xenon 1900h is well suited for a wide variety of healthcare applications that require the versatility of area-imaging technology.

Powered by Adaptus® Imaging Technology 6.0, Xenon 1900h delivers superior bar code scanning and digital image capture. Xenon 1900h incorporates a revolutionary decoding architecture along with a custom sensor, enabling extended depth of field, faster reading, and improved scanning performance on poor quality bar codes. From high density linear to 2D bar codes, Xenon 1900h decodes virtually all bar codes found in healthcare environments with ease.

A new space-saving, reliable design with fewer components minimizes downtime and improves serviceability, resulting in increased productivity. Its small form factor ensures that the Xenon 1900h fits well in virtually any sized hand, reducing operator fatigue.

Built with durability in mind, Xenon 1900h can withstand up to 50 drops to concrete from distances as high as 6 feet. Additionally, Xenon 1900h incorporates disinfectant-ready housing which resists the harmful effects of harsh cleaning agents used commonly in healthcare environments. Backed by a five-year warranty, Xenon 1900h is constructed to deliver years of uninterrupted performance.



#### **Features**

- Custom Sensor Optimized for Bar Code Scanning: Improves scanning aggressiveness and protects investment by providing supply chain stability
- Laser-Free Solution: Class I LED illumination mitigates the risk of eye injury and, unlike laser-based devices, does not require training for safe operation
- Disinfectant-Ready Housing: Protects investment with durable construction that is better able to resist the harmful effects of harsh chemicals
- Remote MasterMind® Scanner Management Software:
   Provides a quick and convenient solution for IT
   administrators seeking to manage all scanners within
   their network from a single remote location

## **Xenon 1900h Technical Specifications**

| Mechanical             |  |  |
|------------------------|--|--|
| Dimensions (LxWxH)     | 104 mm x 71 mm x 160 mm (4.1" x 2.8" x 6.3")   |  |
| Weight                 | 147 g (5.2 oz)   |  |
| Electrical             |  |  |
| Input Voltage          | 4 VDC to 5.5 VDC   |  |
| Operating Power        | 2.3 W (450mA @ 5 VDC)  |  |
| Standby Power          | 0.45 W (90mA @ 5 VDC)  |  |
| Host System Interfaces | USB, Keyboard Wedge, RS232, IBM 46xx (RS485)   |  |
| Environmental          |  |  |
| Operating Temperature  | 0°C to 50°C (32°F to 122°F)  |  |
| Storage Temperature    | -40°C to 70°C (-40°F to 158°F)   |  |
| Humidity               | 0% to 95% relative humidity, non-condensing  |  |
| Drop                   | Designed to withstand 50 1.8 m (6') drops to concrete  |  |
| Environmental Sealing  | IP41   |  |
| Light Levels           | 0 to 100,000 lux (9,290 foot-candles)  |  |
| Scan Performance       |  |  |
| Scan Pattern           | Area Image (838 x 640 pixel array)   |  |
| Motion Tolerance       | Up to 610 cm/s (240 in/s) for 13 mil UPC at optimal focus  |  |
| Scan Angle             | Horizontal 41.4°; Vertical: 32.2°  |  |
| Symbol Contrast        | 20% minimum reflectance difference   |  |
| Pitch, Skew            | 45°, 65°   |  |
| Decode Capability      | Reads standard 1D, PDF, 2D, Postal and OCR symbologies *Note: Decode capabilities dependent on kit configuration |  |
| Warranty               | 5 year factory warranty  |  |

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies

| Typical Performance*  | High Density (HD)                |  |  |
|---|----------------------------------|--|--|
| Narrow Width  |                                  |  |  |
| 5 mil Code 39   | 0 mm - 104.1 mm (0" - 4.1")      |  |  |
| 13 mil UPC  | 10.2 mm - 167.6 mm (0.4" - 6.6") |  |  |
| 20 mil Code 39  | 10.2 mm - 233.7 mm (0.4" - 9.2") |  |  |
| 6.7 mil PDF417  | 0 mm - 109.2 mm (0" - 4.3")      |  |  |
| 10 mil DM**   | 0 mm - 127 mm (0" - 5.0")        |  |  |
| 20 mil QR   | 10.2 mm - 190.5 mm (0.4" - 7.5") |  |  |
| Resolution 1D Code 39   | 3 mil (0.076 mm)                 |  |  |
| Resolution 2D DM**  | 5 mil (0.127 mm)                 |  |  |
| *Performance may be impacted by bar code quality and environmental conditions |                                  |  |  |
| **Data Matrix (DM)  |                                  |  |  |



#### For more information:

www.honeywellaidc.com

### **Honeywell Scanning & Mobility**

9680 Old Bailes Road Fort Mill, SC 29707 800.582.4263 www.honeywell.com

